| F | π | | 2 | 1-1/2 | 1-1/4 | - | 3/4 | 1/2 | ш | | | |
|---|---|------------------|---------------------------|---|----------------|--------------|--------|--------|----------|-------|--------|------|
| MACHININGS | TOLERANCES | | 92.5 | 83 | 73.5 | 6 4.5 | 56 | 5 | Þ | | | |
| | 5 | | 74.5 | 62 | 53 53 | 42.5 | 35.5 | 28 | ω | | | |
| |) (- 30 | | 85 | 75 | 70 | 56 | 49 | 42 | ဂ | | | - |
| | | | 165 | 140 | 118 | 112 | 93 | 93 | ס | | | |
| | >30 -6 0 | | 16.5 | 15 | 14.5 | 14 | 13.5 | 13.5 | Г | | | |
| - - - - | - Xer | LINEAR- | 44 | 37 | 30 | 24 | 19 | 14 | Ŋ | | | |
| | >60-120 >1 | LINEAR-DIMENSION | 1195 | 770 | 540 | 315 | 215 | 147 | weight | | | |
| | 120-200 | | 321150 | 321140 | 321132 | 321125 | 321120 | 321115 | CODE NO. | | | - |
| - | >200-300 | | 3. Working 4. Thread s | 1. Nominal 2. Working | Specification: | | | | |] | | |
| 2. THE TULERANCE CAN BE ACCETED AS THE SHEET. | REMARK: 1.THE UNIT WEIGHT CAN BE ACCEPTED WITH IN ±3%. | | | 1. Nominal pressure:1.6MPa; 2. Working medium: Water, Gas, Oil(Non-corrosive); | | | | | | | | |
| ED AS THE SI | PTED WITH | | NO | 1 | 2 | ω | 4 | σ | 6 | 7 | œ | 9 |
| | | AGRI-LOCK | NAME | BODY | BONNET | BALL | O-RING | STEM | GASKET | NUTS | HANDLE | NUTS |
| 00T 0E 9092 | MM-50MM | -LOCK BALL VALVE | MATERIAL | Zinc Alloy | Zinc Alloy | IRON | PTFE | IRON | PTFE | BRASS | IRON | S.S. |