

Nylon tubes and coils (PTY) Ltd.

(+27)11 792 5111

www.nylontubesandcoils.co.za shaun@ntcpvc.co.za 366 Fabriek St, Strydompark Johannesburg, South Africa

PRODUCT INFORMATION AND SPECIFICATION SHEET

Product name: BARELLI MINING HOSE - SABS 1086-2015

Description: PVC liner with PVC cover. Reinforced with high tenacity polyester yarn.

Available in orange, blue and green.

Application: Designed for South African mining conditions, water & air conveyance,

compressors, jack hammers, pneumatic tools, etc.

Advantages: Super flexible, UV stabilized smooth bore, full flow.

Long lasting, cut and abrasion resistant, very robust, weather resistant.

Temperature ranges 0 - 60 Celsius.

Non toxic PVC.

SABS 1086-2015 CERTIFICATION PROUDLY MADE IN SOUTH AFRICA.

Specifications: BARELLI MINING HOSE - SABS 1086-2015

INTERNAL DIAMETER (mm)	10	12	20	25	32	40	50
PRESSURE (bar) 20 Deg C							
Working (Orange)	17	17	15	14	10		8.8
Bursting (Orange)	68	68	60	56	40		35
Working (Blue)	17	17	15	14	10		8.8
Bursting (Blue)	68	68	60	56	40		35
Working (Green)	17	17	15	14	10	8.8	8.8
Bursting (Green)	68	68	60	56	40	35	35

^{*} burst pressures are minimum requirements







Disclaimer: The specifications listed are a guideline only, and the information provided may vary from time to time. All measurements indicated above are target spec, tolererance levels are within factory spec. We reserve the unconditional right to change the specifications, and will not be held liable for any loss, injury or damage whatsoever