



eco fibre

eco fibre sealer

Introducing **Eco Fibre Sealer**: A new generation water-based acrylic elastic long-life water-proof sealer for roofs, window ledges and parapet walls.

Advantages

- Ultimate Waterproof Protection
- Versatile Colour Options
- Fibrous Particle Technology
- Flexible and Enduring
- Versatile Repair Solutions
- Exceptional Durability and UV-resistance
- Easy Application and Efficiency
- Low Odor and Long-term Flexibility



Easy Application



UV Reflective



Environmentally Friendly



Waterproofing Solution

www.ecorubber.co.za

info@ecorubber.co.za | 042 108 5002/3



eco fibre

eco fibre sealer

PRODUCT USES

- Exterior and Interior Surfaces
- Cement Tiles, Fibre Cement Sheeting (new or weathered).
- Primed Plaster
- Previously Painted Substrates
- Primed Metal & Wooden Substrates
- Flat Cement/Concrete Roofs & Walls
- Nail Head and Roofing Bolts and Roof Tile Ridges

COVERAGE

- Coverage may fluctuate based on the substrate and surface porosity.
- Typically, the coverage is around 2m² per liter. However, for uncoated or initial coats, the coverage may range from 0.5 - 1m² per liter, when applied to sealed & previously painted substrates.
- When applying a 2nd coat or if the surface has been previously coated, you can expect a coverage of 1.5 - 2m² per liter.
- 2 Coats are recommended for best results.
- For coastal areas and for optimal warranty purposes, a 3rd coat is recommended.

HOW TO APPLY

Kindly use your device to scan the provided QR Code for an in-depth guide on application procedures and training instructions.



www.ecorubber.co.za

info@ecorubber.co.za | 042 108 5002/3