



**eco rubber**<sup>®</sup>  
rubberised sealer

Introducing **Eco Rubber™**: A water-borne, Highly Flexible Pure Acrylic Coating

This versatile water-based pure acrylic coating offers superior water resistance, rust inhibition, and UV tolerance. It's suitable for a wide range of surfaces, serving as both a base and topcoat.

**Advantages**

- Highly flexible pure acrylic coating
- Water resistant
- Non-yellowing
- Excellent adhesion
- UV resistant
- Easy no-mess application properties
- Quick drying
- Direct application - no primer needed
- Can be used as a base and top-coat
- Rust inhibitor



Easy Application



UV Reflective



Environmentally Friendly



Waterproofing Solution

[www.ecorubber.co.za](http://www.ecorubber.co.za)

info@ecorubber.co.za | 042 108 5002/3



## PRODUCT USES

### FOR ALL ROOF TYPES / STRUCTURES INCLUDING:

- Fibre-Cement Roof Sheets
- Cement Roof Tiles
- Chromadek
- Zinc Alum and AluZinc
- Galvanized Iron Roof
- Exterior trims such as Facias, Gutters, Window Sills and Cement Garden Pots

## COVERAGE

- Coverage varies based on substrate/surface porosity.
- The coverage is approximately 4 - 6 m<sup>2</sup> per liter per application at a thickness of 100 microns per coat.
- 2 Coats are recommended (1 liter = approximately 2m<sup>2</sup>)
- Allow approximately 30 minutes for touch dry, depending on the humidity.
- Allow approximately 7 - 14 hours drying time, depending on humidity

## HOW TO APPLY

Kindly use your device to scan the provided QR Code for an in-depth guide on application procedures and training instructions.

