

TE-RH 38 E

Rotary Hammer

Item No.: HW2800043

Bar Code: 4006825595451

The rotary hammer TE-RH 38 E with pneumatic hammer mechanism is a high-quality and versatile powerhouse for challenging construction, renovation and chiseling jobs. With hammer drilling as well as chiseling with and without chisel fixation this all-rounder is equipped with the three functions for the universal application. The main grip of the rotary hammer is vibration-absorbing and signals the optimal contact pressure via "Press Control" - an important support for low attrition and quick operations, though. The aluminum gear head of the rotary hammer is constructed robustly. Additionally, 2 LEDs inform about the remaining performance and needs of maintenance by attrition of brushes. Delivery in a practical transport and storage case.

Features

- Hammer drill with pneumatic hammer action for very good drilling
- Robust SDS-Max tool chuck
- 3 functions: hammer drilling, chiseling with and without fixation
- Press-control: visualizes the optimum pressure
- Speed electronics for smooth initial drilling
- Low vibrations thanks to vibration-absorbing main handle
- Soft grip inserts also have a vibration-absorbing impact
- 2 status LEDs: ready for operation and service (brush wear)
- High-grade components for prolonged operation
- Aluminum hear head light but robust
- Overload slip coupling for safety
- Infinitely adjustable drilling depth stop made of solid metal
- Additional handle with ribs for secure fastening
- Delivered in a practical case



Technical Data

- Mains supply 220-240 V | 50 Hz - Power 1050 W - Idle speed 0-500 min^-1 - Impact rate 0-4100 min^-1 - Impact power 9 J - Tool holder SDS Max - Drilling capacity in concrete 38 mm

Logistic Data

- Product weight 6.9 kg - Gross weight single packaging 9.5 kg

452 x 133 x 345 mm - Dimensions single packaging

- Pieces per export carton 2 Pieces - Gross weight export carton 18.6 kg

- Dimensions export carton 380 x 455 x 285 mm - Container quantity (20"/40"/40"HC) 1120 | 2240 | 2750















