

GENERAL HANDLING LATEX GLOVE



MECHANICAL RISK PROFILE

The gloves performance against mechanical risk tests as stipulated by the EN388 standard.

ABRASION 🛑	1	2	
CUT (1		
TEAR 🛑	1	2	
PENETRATION 🛑	1		

LATEX COATING PROPERTIES

Latex is made from natural rubber latex. It has good flexibility, durability and a superior wet & dry grip.

DRY GRIP (1	2	3	4	5	
WET GRIP (2	3	4	5	
			`	•		
OIL GRIP (1					
OIE OI III						
DEXTERITY (1	2	3	4		
DEXILITI		-	ı		$\overline{}$	
DURABILITY (1	2				
DUNADILITY						
DIVERSITY (1	2				

SPECIFICATIONS:

- Seamless 13g purple woven polyester liner has a thicker feel while offering comfort, dexterity and breathability.
- Latex crinkle palm coating provides excellent grip in wet & dry conditions with good abrasion and tear resistance.
- Knit wrist helps prevent dust & debris from entering the glove liner.
- Washable to extend the glove life and reduce replacement costs.
- Breathable back for comfort.
- O Sizes: 7/S, 8/M, 9/L, 10/XL, 11/XXL

APPLICATIONS:

- Assembly / Manufacturing
- O General Duty
- Gardening / Agriculture













