HONDA

TILLER

FQ650 - GENERAL FEATURES

- FQ650 is Honda's newest addition to the axle rotary compact tiller product range
- Fitted with a 4-stroke 6.5HP GP200 engine, FQ650 is the mose powerful Honda tiller
- FQ650 is not only durable and affordable but it is also light and able to turn in small circles
- By fitting various attachments, FQ650 can cultivate hard soil, plough deep soil and create ridges to lift soil for vegetables
- FQ650 is designed both on a safety-first and user-friendly approach making it the most suitable tiller in the market

FQ650	
Dimensions	1625 x 650 x 935mm
Dry Weight	55.0 kg
<u>Engine</u>	
Engine Name	GP200H
Total Displacement (cm3)	196
Valve system, Cooling, Cycle, Cylinder	OHV Air-cooled 4-st. Single-cylinder
Engine Net Power [kW/rpm]	4.2 / 3600
Continuous Rated Power [kW / rpm]	3.7 / 3600
Engine Max. Net Torque [N.m (kg.m)/rpm]	12.4 / 2500
Idling Speed (rpm)	1400 (+200, -150)
Max. Idling Speed (rpm)	3800 (+0, -200)
Starter System	Recoil starter
Recoil Starter Cover	Mud-water resistant type
Air Cleaner System	Dual type
Air Intake	Air Cleaner
Carburetor Drain	Carburetor Body
Fuel Tank Capacity (L)	3.1
Clutch	
Clutch Type	Belt tension type
Operation Method	Manual Lever



<u>Transmission</u>	
No. of Gears	Forward 2 / Reverse 1
Axle Rotating Speed (rpm)	1st. 91.4/ 2nd. 125.7 / R 68.5
<u>Handle</u>	
Height Adjustable	3 shifts adjustable
Shape	Y Shape
Fender	Main + Large-size Sub-Fender
Transportation Wheel Diameter	Ф265mm

DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.