

MO-FLO

SULFURIC ACID DRAIN OPENER

Description:

Quickly dissolves all organic obstructions including: cloth and paper rags, grease, hair, paper, sanitary napkins, sludge, soap, and coffee grounds in drains leading from cesspools, grease traps, sinks, floors, bathtubs, and shower stalls.

Benefits:

- Highly concentrated
- Quickly dissolves grease build-up and solids stopping up the drain
- Keeps lines and drains clean and odor free
- Formulated with virgin-grade 99% Sulfuric Acid



Application:

Add the required amount of Mo-Flo as per chart below. Always use face shield when applying. Keep face and hands to one side of drain - do not look into drain while adding Mo-Flo.

	Quantity to be used	Contact Time	Additional Recommendations
Small Clogged drains	1 cup	5 minutes	Flush with water 2 to 3 minutes
8 to 10 cm drains	1 litre	15 minutes	Flush with water 5 minutes
15 to 20 cm drains	2 litres	15 minutes	Flush with water 15 minutes
Grease Traps	1 litre (or more)	45 minutes	Use 200 - 300 ml periodically for maintenance
Slop Sinks	500 ml	25 minutes	Pour directly into drain
Toilets (reduce water level with plunger)	Up to 500 ml at a time	15 minutes	Pour at least 3 litres water into bowl

NOTE: Quantity to use may vary depending upon conditions and size. Do not allow to stand on porcelain surfaces as heat build-up may cause cracking. Do not use hot water immediately before or after using Mo-Flo. Use cold water only. Use in well ventilated area only.

Specifications:

pH <1
 Density @ 25°C (ASTM-D-287)..... 1.84 gm/ml
 Color Cloudy dark brown
 Appearance Viscous Liquid
 Odor No Odor
 Health/Flammability/Reactivity 3/0/2
 Personal Protection C



8 Induland Crescent, Lansdowne, Cape Town
 Tel: 021-6921295 - Fax: 021-6913898
 info@momar.co.za - www.momar.co.za