



Sandable & overpaintable once dry



Can hold up to 50 kg/m<sup>2</sup> initial tack. No clamping required



**Dries Transparent** 



Multi-materials: Used on wood, stone aluminum, plaster, concrete & polyurethane rigid-foams



# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 17

### Pattex NMN INVISIBLE TUBE (UK)

SDS No. : 609201 V003.0 Revision: 09.12.2019 printing date: 29.06.2021 Replaces version from: 31.01.2018

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

- Pattex NMN INVISIBLE TUBE (UK)
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Assembly adhesive, dispersion

### **1.3. Details of the supplier of the safety data sheet** Henkel South Africa (PTY) Ltd. Cnr Bosworth & Potgieter St

1449 Alberton

South Africa

Phone: +27 (116172400)

ua-productsafety\_za@henkel.com

### 1.4. Emergency telephone number

0800 202 202

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### **Classification (CLP):**

Chronic hazards to the aquatic environmentCategory 3H412Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Label elements (CLP):

Hazard statement:

H412 Harmful to aquatic life with long lasting effects.

Supplemental information	Contains: 1,2-Benzisothiazol-3(2H)-one May produce an allergic reaction. Contains preservative(s): Isothiazolinone mixture 3:1 (CIT/MIT). May produce an allergic reaction.
Precautionary statement:	<ul> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P262 Do not get in eyes, on skin, or on clothing.</li> <li>P273 Avoid release to the environment.</li> <li>P501 Dispose of contents/container in accordance with national regulation.</li> </ul>

### 2.3. Other hazards

None if used properly. Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

General chemical description: 1-Component assembly adhesive Base substances of preparation: Styrene-acrylate copolymer water

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.	content	Clussification
Distillates (petroleum), hydrotreated light	265-149-8	1 - < 5%	Asp. Tox. 1
64742-47-8			H304
			Aquatic Chronic 2
			H411
Dodecan-1-ol, EO~	500-002-6	0,1-<1%	Acute Tox. 4; Oral
9002-92-0			H302
			Eye Dam. 1
			H318
			Aquatic Acute 1
			H400
			Aquatic Chronic 3
			H412
1,2-Benzisothiazol-3(2H)-one	220-120-9	50- < 500 PPM	Aquatic Acute 1
2634-33-5			H400
			Aquatic Chronic 1
			H410
			Acute Tox. 4
			H302
			Skin Irrit. 2
			H315
			Skin Sens. 1
			H317
			Eye Dam. 1
			H318
			Acute Tox. 2
			H330
Isothiazolinone mixture 3:1 (CIT/MIT)		1- < 15 PPM	Acute Tox. 2; Inhalation
55965-84-9			H330
			Aquatic Chronic 1
			H410
			Acute Tox. 3; Oral
			H301
			Acute Tox. 2; Dermal H310
			Eye Dam. 1 H318
			Skin Sens. 1A
			H317
			Aquatic Acute 1
			H400
			Skin Corr. 1C
			H314
			П314

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Distillates (petroleum), hydrotreated light 64742-47-8	265-149-8	1-< 5 %	Xn - Harmful; R65
Dodecan-1-ol, EO~ 9002-92-0	500-002-6	0,1 - < 1 %	Xn - Harmful; R22 Xi - Irritant; R41 N - Dangerous for the environment; R50
1,2-Benzisothiazol-3(2H)-one 2634-33-5	220-120-9	50 - < 500 PPM	Xi - Irritant; R38, R41 R43 N - Dangerous for the environment; R50 Xn - Harmful; R22
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9		1 - < 15 PPM	T+ - Very toxic; R26 T - Toxic; R24/25 C - Corrosive; R34 Xi - Irritant; R43 N - Dangerous for the environment; R50/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

#### Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed** See section: Description of first aid measures

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus. Wear protective equipment.

**SECTION 6: Accidental release measures** 

6.1. Personal precautions, protective equipment and emergency procedures Wear protective equipment. Danger of slipping on spilled product. Avoid contact with skin and eyes.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up Remove mechanically. Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

**SECTION 7: Handling and storage** 

#### 7.1. Precautions for safe handling

Avoid skin and eye contact.

### Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, frost-free place.

Avoid strictly temperatures below + 5  $^{\circ}$ C and above + 50  $^{\circ}$ C.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

### 7.3. Specific end use(s)

Assembly adhesive, dispersion

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational Exposure Limits**

Valid for South Africa

None

# Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
		periou	mg/l	ppm	mg/kg	others	
1,2-Benzisothiazol-3(2H)-one	aqua		0,00403		00		
2634-33-5	(freshwater)		mg/l				
1,2-Benzisothiazol-3(2H)-one	aqua (marine		0,000403				
2634-33-5	water)		mg/l				
1,2-Benzisothiazol-3(2H)-one	aqua		0,0011				
2634-33-5	(intermittent releases)		mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sewage treatment plant (STP)		1,03 mg/l				
1,2-Benzisothiazol-3(2H)-one	sediment				0,0499		
2634-33-5	(freshwater)				mg/kg		
1,2-Benzisothiazol-3(2H)-one	sediment				0,00499		
2634-33-5	(marine water)				mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Soil				3 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (freshwater)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (marine water)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sewage treatment plant (STP)		0,23 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (freshwater)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (marine water)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Soil				0,01 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (intermittent releases)		0,00339 mg/l				

### Page 7 of 17

### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	inhalation	Long term exposure - systemic effects		6,81 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	dermal	Long term exposure - systemic effects		0,966 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	inhalation	Long term exposure - systemic effects		1,2 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	dermal	Long term exposure - systemic effects		0,345 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	oral	Long term exposure - systemic effects		0,09 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

#### Biological Exposure Indices: None

#### 8.2. Exposure controls:

#### Respiratory protection:

Suitable breathing mask when there is inadequate ventilation. Combination filter: ABEKP (EN 14387) This recommendation should be matched to local conditions.

#### Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. Perforation time > 10 minutes

material thickness > 0.1 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

# Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

#### Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

### **SECTION 9: Physical and chemical properties**

7.0 - 8.5

# 9.1. Information on basic physical and chemical properties

Appearance	paste
	paste
	white
Odor	neutral
Odour threshold	No data available / Not applicable

#### pН

	7,0 0,5
(20 °C (68 °F))	
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density	1,0 - 1,05 g/cm3
(20 °C (68 °F))	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

None if used for intended purpose.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### **10.4.** Conditions to avoid

None if used for intended purpose.

#### 10.5. Incompatible materials

None if used properly.

#### 10.6. Hazardous decomposition products

None known.

# **SECTION 11: Toxicological information**

#### General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

### **11.1. Information on toxicological effects**

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (petroleum), hydrotreated light 64742-47-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	LD50	490 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (petroleum), hydrotreated light 64742-47-8	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

### Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Distillates (petroleum), hydrotreated light 64742-47-8	LC50	> 5,3 mg/l	dust/mist	4 h	rat	not specified
1,2-Benzisothiazol-3(2H)- one 2634-33-5	LC50	0,4 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

#### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light 64742-47-8	slightly irritating		rabbit	Expert judgement
1,2-Benzisothiazol-3(2H)- one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

### Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light 64742-47-8	not irritating		rabbit	EPA OTS 798.4500 (Acute Eye Irritation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Category 1 (irreversible effects on the eye)		rabbit	not specified

#### Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No. Distillates (petroleum), hydrotreated light 64742-47-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

### Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of	Metabolic activation /	Species	Method
		administration	Exposure time		
Distillates (petroleum), hydrotreated light	negative	bacterial reverse mutation assay (e.g	with and without		OECD Guideline 471 (Bacterial Reverse Mutation
64742-47-8		Ames test)			Assay)
Distillates (petroleum), hydrotreated light 64742-47-8	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum),	negative	mammalian cell	with and without		OECD Guideline 479 (Genetic
hydrotreated light 64742-47-8		gene mutation assay			Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
1,2-Benzisothiazol-3(2H)- one	negative	bacterial reverse mutation assay (e.g	with and without		OECD Guideline 471 (Bacterial Reverse Mutation
2634-33-5 1,2-Benzisothiazol-3(2H)-	negative	Ames test) mammalian cell	with and without		Assay) OECD Guideline 476 (In vitro
one 2634-33-5	negative	gene mutation assay	with and without		Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)-	positive	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
one 2634-33-5	without metabolic activation	chromosome aberration test			Mammalian Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture	positive	in vitro mammalian	with and without		EPA OPP 84-2 (Mutagenicity
3:1 (CIT/MIT) 55965-84-9	-	chromosome aberration test			Testing)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Distillates (petroleum), hydrotreated light 64742-47-8	negative	intraperitoneal		rat	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

### Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

### **Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Distillates (petroleum), hydrotreated light 64742-47-8	NOAEL P >= 494 mg/kg NOAEL F1 >= 494 mg/kg	screening	dermal	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL P 112 mg/kg NOAEL F1 56,6 mg/kg NOAEL F2 56,6 mg/kg	Two generation study	oral: feed	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

### STOT-single exposure:

No data available.

### STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 150 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 69 mg/kg	oral: feed	90 days daily	rat	EPA OPP 82-1 (90-Day Oral Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 0.34 mg/m3	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 2,625 mg/kg	dermal	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

#### Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Distillates (petroleum), hydrotreated light 64742-47-8	3,1 mm2/s	40 °C	not specified	

### **SECTION 12: Ecological information**

#### General ecological information:

Do not empty into drains, soil or bodies of water.

### 12.1. Toxicity

### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light 64742-47-8	LL50	> 2 - 5 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish, Juvenile Growth Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Distillates (petroleum),	EL50	1,4 mg/l	48 h	Daphnia magna	OECD Guideline 202
hydrotreated light		-			(Daphnia sp. Acute
64742-47-8					Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202
2634-33-5		-			(Daphnia sp. Acute
					Immobilisation Test)
Isothiazolinone mixture 3:1	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202
(CIT/MIT)				_	(Daphnia sp. Acute
55965-84-9					Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Distillates (petroleum), hydrotreated light 64742-47-8	NOEL	0,48 mg/l	21 d		OECD 211 (Daphnia magna, Reproduction Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	1,2 mg/l	21 d		OECD 211 (Daphnia magna, Reproduction Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,0036 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)

### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No. Distillates (petroleum), hydrotreated light 64742-47-8	type EL50	8,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), hydrotreated light 64742-47-8	NOEL	4 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,11 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,0403 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	23 mg/l		predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC20	0,97 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

### 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Distillates (petroleum), hydrotreated light 64742-47-8	readily biodegradable, but failing 10-day window	aerobic	61 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	not readily biodegradable.	aerobic	42,1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

### 12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 day		not specified	other guideline:
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

### 12.4. Mobility in soil

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Distillates (petroleum),	> 4		QSAR (Quantitative Structure Activity Relationship)
hydrotreated light			
64742-47-8			
1,2-Benzisothiazol-3(2H)-one	0,7	20 °C	EU Method A.8 (Partition Coefficient)
2634-33-5			
Isothiazolinone mixture 3:1	-0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
(CIT/MIT)			Method)
55965-84-9			

### 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Distillates (petroleum), hydrotreated light	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
64742-47-8	Bioaccumulative (vPvB) criteria.
1,2-Benzisothiazol-3(2H)-one	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2634-33-5	Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture 3:1 (CIT/MIT)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
55965-84-9	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

### Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080409

## **SECTION 14: Transport information**

14.1.	UN number				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADN	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	Not dangerous goods			
14.2.	UN proper shipping name				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADN	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	Not dangerous goods			
14.3.	Transport hazard class(es)				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADN	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	Not dangerous goods			
14.4.	Packing group				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADN	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	Not dangerous goods			
14.5.	Environmental hazards				
	ADR	not applicable			
	RID	not applicable			
	ADN	not applicable			
	IMDG	not applicable			
	IATA	not applicable			
14.6.	Special precautions for user				
	ADR	not applicable			
	RID	not applicable			
	ADN	not applicable			
	IMDG	not applicable			
	IATA	not applicable			
14.7.	Transport in bulk according to Annex II of Marpol and the IBC Code				
	not applicabl	le			

# **SECTION 15: Regulatory information**

 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

 VOC content
 0,0 %

 (VOCV 814.018 VOC regulation

#### CH)

#### **15.2.** Chemical safety assessment

A chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R22 Harmful if swallowed.

R24/25 Toxic in contact with skin and if swallowed.

R26 Very toxic by inhalation.

- R34 Causes burns.
- R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

- R50 Very toxic to aquatic organisms.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

- H304 May be fatal if swallowed and enters airways.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

#### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This Safety Data Sheet has been generated based on Regulation (EC) No 1907/2006 and it is applicable for Gulf Cooperation Council (GCC) and Africa only. No warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory, including export laws and regulations. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory affairs for additional assistance.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.