



TECHNICAL DATA SHEET: PLASTERS, FILLERS & SKIMMERS



CRACK GUARD

IMPROVES STRENGTH & FLEXIBILITY OF WALL COATINGS WHEN BRIDGING HAIRLINE CRACKS

FEATURES AND BENEFITS:

- Improved strength and flexibility of decorative coatings
- Improves badly plastered surfaces
- Bridges hairline cracks

DIRECTIONS FOR USE

1. Repair the surface by filling major cracks with the appropriate Powafix filler.
2. Remove all loose and flaking material. Thoroughly clean the surface with Powafix Sugar Soap (as directed).
3. Apply a base coat of paint and stick Crack Guard to the wet base coat. Ensure Crack Guard is applied vertically.
4. Smooth off Crack Guard by pressing or painting out all blemishes and air bubbles. Avoid over lapping the edges.
5. Apply a generous coat of paint over the repaired area and allow to dry.
6. The fiber pattern over Crack Guard may still be visible. Apply a final coat of paint to finish off.

PRECAUTION:

Paint quality will impact on the performance of the Crack Guard.

Store out of reach of children and animals. If swallowed do not induce vomiting & seek immediate medical attention.

ISSUE DATE: AUGUST 2023

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.