

PLASTERS, FILLERS AND SKIMMERS

PRODUCT NAME

MAXI PLAST
PLASTER KEYING AND BONDING LIQUID

DESCRIPTION

Water based ready to use. Easily mixes into plasters and improves application properties, adhesion and bonding strength. The resulting flexible plaster is easier to paint and enhances the life span of decorative coatings

PACKAGING FABS

- Water based ready to use
- Increases plaster adhesion and bonding strength
- Improved flexibility prevents cracking

USAGE PRECAUTIONS

Read all instructions before use. Only apply to dry / damp free surfaces with a moisture content less than 10%. Prime all plaster or concrete surfaces with a suitable Powafix Plaster primer*. Only use with fresh moisture free cement / plaster. Maxi Plast is not suitable to be used as a final coat. Do not paint in cold weather below 8°C or if imminent rainfall is expected. In areas affected by heavy dew do not paint after 2pm. Do not apply coating or plaster mix on any contaminated or unsound surface as this will affect the adhesion. Contact our technical help line for assistance prior to painting.

DIRECTIONS FOR USE SURFACE PREPARATION

Remove all loose / flaking material. Sand smooth any glossy surfaces Treat algae or fungi with Powafix Fungi Fix*. Thoroughly clean any surface contaminates with Powafix Sugar Soap*.

APPLICATION INSTRUCTIONS

Bonding liquid – Improves surface adhesion and damp resistance. Shake product well before use. Apply product with a brush, thoroughly working product into all cracks and holes. Allow 2 –



PLASTERS, FILLERS AND SKIMMERS

4 hours drying time $(6 - 8m^2 / L)$. This may increase on porous or rough surfaces. Clean brushes with Powafix Solvent Based Brush Cleaner*. Product thinning is not recommended.

Plaster Additive – Improves the durability of the plaster, adhesion properties and damp resistance. Shake product well before use. Thoroughly mix cement and sand. Maxi Plast is ready to use and no additional water is required. Pour directly into plaster mix as required. Once mixed to a lump free, uniform consistency plaster mix is ready to apply. Clean equipment with Powafix Solvent Based Brush Cleaner*.

STORAGE PRECAUTIONS

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Store away from heat, sparks, open flames and hot surfaces. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact **0860 254 680** for disposal information.

SAFETY

May cause allergic skin reaction. Read all instructions before use. Use product in well ventilated areas. Keep out of reach of children. Store in a secure location. If medical advice is needed, have product packaging at hand. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust. IF IN EYES flush with water. Seek medical attention if symptoms persist. IF ON SKIN wash with soapy water. Seek medical attention if symptoms persist. IF SWALLOWED do not induce vomiting and seek immediate medical attention. Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777.

PRODUCT INFORMATION

Barcode	Product code	Colour	Pack size	Case size
6009600999169	MAXPLA1L	n/a	1L	6
6009600999176	MAXPLA5L	n/a	5L	4
6009600999183	MAXPLA25L	n/a	25L	1



PLASTERS, FILLERS AND SKIMMERS

PRODUCT SPECIFICATION:

Appearance	White liquid	
Odour	Mild ammonia	
PH	8.0 – 9.5	
Viscosity	n/a	
Density @ 20°C	1.02 – 1.06	
Flash point	n/a	

DISCLAIMER

The information contained on this document, is to the best of our knowledge, accurate. As the use of the product and site conditions are beyond our control, no further warranty is given or implied in respect of information given.