



More than just a product.

TECHNICAL DATA SHEET

TIMBER TREATMENT



WAKS COAT TIMBER OIL TECHNICAL DATASHEET

PRODUCT NAME

WAKS COAT
AFRICAN TIMBER OIL

DESCRIPTION – TEXT FROM PRODUCT FLYER

Powafix's African timber oil stands up to the harsh extremes of our weather. The unique formulation of deep penetrating oils and wax prolongs the life of exterior timber and resists fungal growth. Effective at sealing and repelling water which prevents timber cracking and splitting.

PACKAGING FABBS

- Seals timber and prevents cracking & splitting
- Oil / wax blend for improved water repellence
- Deep oil penetration prolongs timber life & inhibits fungal growth

USAGE PRECAUTIONS

Read all instructions before use. Remove all wood rot and apply only to dry timber. Treat any wood rot or insect damage with Powafix Enseal* and refer to Powafix Enseal mixing instructions below. In areas susceptible to insect attack use pre treated timber. If Powafix Waks Coat is to be used on timber below ground (anchor posts) treat with a minimum of three coats. Product coats timber to clear amber colour. Do not apply coating on any contaminated or unsound surface as this will affect the adhesion and penetration. Stains timber a light brown colour. Product remains tacky and leaves a waxy residue after drying. Contact our technical help line for assistance prior to painting

DIRECTIONS FOR USE

SURFACE PREPARATION

Remove all loose / flaking material.

Sand smooth any glossy or uneven surfaces. Applying to sealed timber will limit product penetration and effectiveness. Thoroughly clean any surface contaminates with Powafix Sugar Soap* and Powafix Fungi Fix* for algae or fungi. Use Powafix Spackle wood filler* to fill surface imperfections. If necessary, treat any wood rot with Powafix Enseal* prior to filling.



APPLICATION INSTRUCTIONS

Stir well before use. Apply product with a brush thoroughly working product into all indentations or holes. Allow 2 – 4 hours drying time between coats. (4 - 6 m² / litre) This may increase on porous or rough surfaces. Clean brushes with Powafix Solvent Based Brush Cleaner* or Powafix Lacquer thinners*. Product thinning is not recommended. Apply a maintenance coat every 18 months. Powafix Waks Coat can be mixed with Powafix Enseal to improve resistance to wood borer / white ants. Measure out as per addition levels below, pour into Powafix Waks Coat and mix thoroughly. Mixed product must be used within 2 to 3 days

STORAGE

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Store away from heat, sparks, open flames and hot surfaces. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact **0860 254 680** for disposal information

SAFETY

Flammable liquid and vapour. Acute skin toxicity. Acute inhalation toxicity. Skin irritation. Serious eye damage. Potential carcinogen. Specific organ toxicity (repeated exposure). Toxic to the environment with long lasting effects. Read all instructions before use. Use product within well-ventilated areas. Keep out of reach of children. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. If medical advice is needed, have product packaging at hand. Use personal protective equipment as required. Wear protective gloves. Wear eye protection. Wear a respirator do not inhale fumes. **IF IN EYES** flush with water and seek immediate medical attention. **IF ON SKIN** wash with soapy water. Seek medical attention if symptoms persist. **IF SWALLOWED** do not induce vomiting and seek immediate medical assistance. **IF INHALED** move victim to fresh air and seek immediate medical assistance. Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre: **0861 555 777**.



PRODUCT GUARANTEE

In the unlikely event you are not totally satisfied – this product has a 12 month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned unaltered, in its original packaging with proof of purchase. This warranty excludes product failure caused by misuse of product outside of recommended uses and instructions on the packaging

PRODUCT INFORMATION

BARCODE	PRODUCT CODE	COLOUR	PACK SIZE	CASE SIZE
6009600999145	WACO1L		1LT	6
6009600999152	WACO5L		5LT	4
6009600999275	WACO25L		25LT	1

PRODUCT SPECIFICATION:

APPEARANCE	
ODOUR	
PH	
VISCOSITY	
DENSITY @ 20°C	
FLASH POINT	

DISCLAIMER

The information contained on this document, is to the best of our knowledge, accurate. As the use of the product and site conditions are beyond our control, no further warranty is given or implied in respect of information given.