

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Issue date:28/08/2020 Revision date: 29/08/2022 : Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Trade name : Air Scents fresh dry room spray - Cotton fresh

Type of product : Air freshener
Product code : SH1289
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Supplier's details

Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa T (011) 421 7111

info@shieldchem.co.za

1.4. Emergency telephone number

Emergency number : (011) 421 7111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2A H319
Hazardous to the aquatic environment — Acute Hazard, Category 2 H401
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA)



 \diamondsuit

GHS07

GHS02

Signal word (GHS-ZA) : Danger

Hazardous ingredients : propane; butane, liquefied, under pressure; Ethanol; benzyl benzoate

Hazard statements (GHS-ZA) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H401 - Toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS-ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P264 - Wash hands, forearms and face thoroughly after handling. P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects

: Pressurised container: May burst if heated,Extremely flammable aerosol,Causes serious eye irritation,Toxic to aquatic life,Harmful to aquatic life with long lasting effects.

28/08/2020 EN (English) 1/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 3: Composition/information on ingredients

Not applicable

Mixtures 3.2.

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	(CAS-No.) 106-97-8	40.0 - 50.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401
Ethanol		30.0 - 40.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
propane	(CAS-No.) 74-98-6	20.0 - 30.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
benzyl benzoate	(CAS-No.) 120-51-4	1.0 - 5.0	Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion Call a poison center or a doctor if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : Eye irritation.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

: Pressurised container: May burst if heated. **Explosion hazard**

Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Avoid release to the environment.

Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

: Dispose of materials or solid residues at an authorized site. Other information

28/08/2020 EN (English) 2/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-

ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Propane
OEL TWA (mg/m³)	1800 mg/m³
OEL TWA (ppm)	1000 ppm
Regulatory reference	Government Notice No. R 904
butane, liquefied, under pressure (10	6-97-8)
South Africa - Occupational Exposur	e Limits (Recommended Limits)
Local name	Butane
OEL TWA (mg/m³)	1430 mg/m³
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m³)	1780 mg/m³
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	n-Butane
OEL TWA (mg/m³)	1430 mg/m³
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m³)	1780 mg/m³
OEL STEL (ppm)	750 ppm

Government Notice No. R 904

8.2. Appropriate engineering controls

Regulatory reference

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves

Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : clear.
Odour : Cotton.

Odour threshold : No data available pH : No data available pH solution : No data available Relative evaporation rate (butylacetate=1) : No data available

28/08/2020 EN (English) 3/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure No data available Vapour pressure at 50 °C : No data available Relative vapour density at 20 °C : No data available Relative density No data available Relative density of saturated gas/air mixture No data available : No data available Density Relative gas density : No data available Solubility : No data available No data available Log Pow Log Kow No data available No data available Viscosity, kinematic Viscosity, dynamic No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available Explosive limits : No data available Lower explosive limit (LEL) : No data available Upper explosive limit (UEL) : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

propane (74-98-6)		
LC50 inhalation rat (ppm) > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))		
butane, liquefied, under pressure (106-97-8)		
LC50 inhalation rat (mg/l)	1442.738 - 1443 mg/l 15 MIN	
LC50 inhalation rat (ppm)	800000 ppm 15 MIN	
Ethanol		
LD50 oral rat	10470 mg/kg	
LD50 dermal rabbit	> 15800 mg/kg	
LC50 inhalation rat (mg/l)	51 mg/l/4h	

28/08/2020 EN (English) 4/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

benzyl benzoate (120-51-4)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Air Scents fresh dry room spray - Cotton fresh	1
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-

Air Scents fresh dry room spray - Cotton fresh

term (acute)

: Toxic to aquatic life.

Hazardous to the aquatic environment, long-

term (chronic)

: Harmful to aquatic life with long lasting effects.

propane (74-98-6)		
LC50 fish 1	24 mg/l (96 h, Pisces, Literature study)	
LC50 fish 2	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)	
EC50 Daphnia 1	7 mg/l (48 h, Daphnia magna, Literature study)	
BCF fish 1	9 - 25 (Pisces, QSAR)	
Log Pow	1.09 - 2.8 (Experimental value, 20 °C)	
butane, liquefied, under pressure (106-97-8)		
LC50 fish 1	> 1000 mg/l (96 h, Pimephales promelas, QSAR)	
EC50 72h algae (1)	5.3 - 5.5 mg/l (Algae, QSAR)	
Log Pow	2.89 (Experimental value)	
Ethanol		
LC50 fish 1	11.2 mg/l	
EC50 Daphnia 1	5012 mg/l	
Bioconcentration factor (BCF REACH)	< 10	
benzyl benzoate (120-51-4)		
LC50 fish 1	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)	
EC50 Daphnia 1	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
EC50 72h algae (1)	0.475 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)	
BCF fish 1	2.286 (BCFBAF v3.00, Pisces, QSAR)	
Log Pow	3.97 (Experimental value, 25 °C)	
Log Koc	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)	
12.2. Persistence and degradability		

Persistence and degradability No additional information available propane (74-98-6) Persistence and degradability Readily biodegradable in water. butane, liquefied, under pressure (106-97-8) Persistence and degradability Readily biodegradable in water.

28/08/2020 EN (English) 5/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Ethanol	
Chemical oxygen demand (COD)	2.04 g O₂ /g substance
benzyl benzoate (120-51-4)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	Readily blodegradable in water.
Air Scents fresh dry room spray - Cotton fr	esh
Bioaccumulative potential	No additional information available
propane (74-98-6)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
butane, liquefied, under pressure (106-97-8	
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Ethanol	, , ,
Bioconcentration factor (BCF REACH)	See section 12.1 on ecotoxicology
, ,	Coo Scotion 12.1 on Coolonicology
benzyl benzoate (120-51-4) BCF fish 1	See agetian 12.1 on contovice legy
Log Pow	See section 12.1 on ecotoxicology See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
12.4. Mobility in soil	Low potential for bloadediffulation (Log Now < 4).
Air Scents fresh dry room spray - Cotton fr	esh
Mobility in soil	No additional information available
propane (74-98-6)	
Surface tension	0.016 N/m (-47 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).
butane, liquefied, under pressure (106-97-8	
Surface tension	< 0.1 N/m (0 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).
Ethanol	,
Mobility in soil	1
benzyl benzoate (120-51-4)	·
Surface tension	0.027 N/m (210 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for mobility in soil.
12.5. Other adverse effects	
Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1

28/08/2020 EN (English) 6/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SANS	IMDG	IATA
*		Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
	:	
No supplementary information available		

14.6. Special precautions for user

- SANS

Special provisions (SANS) : 63, 190
Limited quantities (SANS) : See SP277
Limited quantities (SANS) : See SP277
Packagings, large packagings and IBCs : P003

Packing instructions (SANS)

Packagings, large packagings and IBCs Special : PP17, PP87

packing instructions (SANS)

- IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None

- IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

 Issue date
 : 28/08/2020

 Revision date
 : 29/08/2022

Full text of H-statements:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H301	Toxic if swallowed.
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways.

28/08/2020 EN (English) 7/8

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

28/08/2020 EN (English) 8/8