

### Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Issue date:28/08/2020 Revision date: 29/08/2022 : Version: 1.0

### **SECTION 1: Identification**

#### 1.1. Product identifier

Product form : Mixture

Trade name : Air Scents fresh dry room spray - Amber & oud

Type of product : Air freshener
Product code : SH1290
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### No additional information available

#### 1.3. Supplier's details

#### Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - South Africa T (011) 421 7111

info@shieldchem.co.za

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to the United Nations GHS

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2A H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Acute Hazard, Category 2 H401
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

#### 2.2. Label elements

### Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA)





GHS02

2 GHS07

Signal word (GHS-ZA) : Danger

Hazardous ingredients : propane; butane, liquefied, under pressure; Ethanol; diethyl phthalate

Hazard statements (GHS-ZA) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H401 - Toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS-ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice. P337+P313 - If eye irritation persists: Get medical advice.

28/08/2020 EN (English) 1/8

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P362+P364 - Take off contaminated clothing and wash it before reuse.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to an approved waste disposal plant.

#### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects

: Pressurised container: May burst if heated, Extremely flammable aerosol, May cause an allergic skin reaction, Causes serious eye irritation, Toxic to aquatic life, Harmful to aquatic life with long lasting effects.

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	(CAS-No.) 106-97-8	40.0 - 50.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401
Ethanol		30.0 - 40.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2A, H319 Aquatic Acute Not classified
propane	(CAS-No.) 74-98-6	20.0 - 30.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
diethyl phthalate	(CAS-No.) 84-66-2	1.0 - 5.0	Flam. Liq. Not classified STOT RE Not classified Aquatic Acute 3, H402 Aquatic Chronic Not classified

Full text of H-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

## 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing spray.

28/08/2020 EN (English) 2/8

### Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

propane (74-98-6)		
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Propane	
OEL TWA (mg/m³)	1800 mg/m³	
OEL TWA (ppm)	1000 ppm	
Regulatory reference	Government Notice No. R 904	
butane, liquefied, under pressure (106-97-8)		
South Africa - Occupational Exposure Limits (Reco	mmended Limits)	
Local name	Butane	
OEL TWA (mg/m³)	1430 mg/m³	
OEL TWA (ppm)	600 ppm	
OEL STEL (mg/m³)	1780 mg/m³	
OEL STEL (ppm)	750 ppm	
Regulatory reference	Government Notice. R: 1179	
South Africa - Occupational Exposure Limits (Airbo	orne Pollutants)	
Local name	n-Butane	
OEL TWA (mg/m³)	1430 mg/m³	
OEL TWA (ppm)	600 ppm	
OEL STEL (mg/m³)	1780 mg/m³	
OEL STEL (ppm)	750 ppm	
Regulatory reference	Government Notice No. R 904	
diethyl phthalate (84-66-2)		
South Africa - Occupational Exposure Limits (Reco	mmended Limits)	
Local name	Diethyl phthalate	
OEL TWA (mg/m³)	5 mg/m³	
OEL STEL (mg/m³)	10 mg/m³	
Regulatory reference	Government Notice. R: 1179	
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Diethyl phthalate	
OEL TWA (mg/m³)	5 mg/m³	
OEL STEL (mg/m³)	10 mg/m³	
Regulatory reference	Government Notice No. R 904	

28/08/2020 EN (English) 3/8

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.4. Exposure limit values for the other components

No additional information available

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Liquid.Colour: clear.

Odour : Amber & oud. Odour threshold No data available No data available Hq No data available pH solution Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) No data available : Not applicable Melting point Freezing point : No data available Boiling point : No data available No data available Flash point No data available Auto-ignition temperature Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure No data available Vapour pressure at 50 °C No data available Relative vapour density at 20 °C : No data available Relative density : No data available Relative density of saturated gas/air mixture No data available Density No data available Relative gas density No data available Solubility : No data available Log Pow : No data available Log Kow No data available Viscosity, kinematic No data available Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available
Explosive limits : No data available
Lower explosive limit (LEL) : No data available
Upper explosive limit (UEL) : No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

## 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

28/08/2020 EN (English) 4/8

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

propane (74-98-6)		
LC50 inhalation rat (ppm) > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))		
butane, liquefied, under pressure (1	06-97-8)	
LC50 inhalation rat (mg/l)	1442.738 - 1443 mg/l 15 MIN	
LC50 inhalation rat (ppm)	800000 ppm 15 MIN	
Ethanol		
LD50 oral rat	10470 mg/kg	
LD50 dermal rabbit	> 15800 mg/kg	
LC50 inhalation rat (mg/l)	51 mg/l/4h	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

diethyl phthalate (84-66-2)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat

Aspiration hazard : Not classified

Air Scents fresh dry room spray - Amber & oud	
Vaporizer	Aerosol

## SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short- : Toxic to aquatic life.

term (acute)

Hazardous to the aquatic environment, long- : Harmful to aquatic life with long lasting effects.

term (chronic)

propane (74-98-6)		
LC50 fish 1	24 mg/l (96 h, Pisces, Literature study)	
LC50 fish 2	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)	
EC50 Daphnia 1	7 mg/l (48 h, Daphnia magna, Literature study)	
BCF fish 1	9 - 25 (Pisces, QSAR)	
Log Pow	1.09 - 2.8 (Experimental value, 20 °C)	
butane, liquefied, under pressure (106-97-8)		
LC50 fish 1	> 1000 mg/l (96 h, Pimephales promelas, QSAR)	
EC50 72h algae (1)	5.3 - 5.5 mg/l (Algae, QSAR)	
Log Pow	2.89 (Experimental value)	
Ethanol		
LC50 fish 1	11.2 mg/l	

28/08/2020 EN (English) 5/8

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Ethanol	
EC50 Daphnia 1	5012 mg/l
Bioconcentration factor (BCF REACH)	< 10
diethyl phthalate (84-66-2)	<u> </u>
LC50 fish 1	29 mg/l Test organisms (species): Cyprinodon variegatus
LC50 fish 2	12 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h algae (1)	23 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	45 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	5 mg/l Test organisms (species): Cyprinus carpio Duration: '28 d'
12.2. Persistence and degradability	
Air Scents fresh dry room spray - Amber	& oud
Persistence and degradability	No additional information available
propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.
butane, liquefied, under pressure (106-97-	-8)
Persistence and degradability	Readily biodegradable in water.
Ethanol	·
Chemical oxygen demand (COD)	2.04 g O <sub>2</sub> /g substance
12.3. Bioaccumulative potential	2.04 g O <sub>2</sub> /g 3ubstance
•	0
Air Scents fresh dry room spray - Amber	-
Bioaccumulative potential	No additional information available
propane (74-98-6)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
butane, liquefied, under pressure (106-97-	
Log Pow	See section 12.1 on ecotoxicology
0	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Ethanol	
Bioconcentration factor (BCF REACH)	See section 12.1 on ecotoxicology
12.4. Mobility in soil	
Air Scents fresh dry room spray - Amber	& oud
Mobility in soil	No additional information available
propane (74-98-6)	
Surface tension	0.016 N/m (-47 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).
butane, liquefied, under pressure (106-97-	-8)
Surface tension	< 0.1 N/m (0 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).
Ethanol	11 11 000
	1
Mobility in soil  12.5. Other adverse effects	
	· Not algorified
Ozone	: Not classified
Other adverse effects	: No additional information available

Other adverse effects : No additional information available

## **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## **SECTION 14: Transport information**

In accordance with SANS / IMDG / IATA

28/08/2020 EN (English) 6/8

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SANS	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	•	
2.1	2.1	2.1
	2	Not applicable
14.4. Packing group	1	1
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
	:	
No supplementary information available		

#### 14.6. Special precautions for user

#### - SANS

Special provisions (SANS) : 63, 190 Limited quantities (SANS) : See SP277 : See SP277 Limited quantities (SANS) Packagings, large packagings and IBCs : P003

Packing instructions (SANS)

Packagings, large packagings and IBCs Special : PP17, PP87

packing instructions (SANS)

## - IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None

#### - IATA

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Y203 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 14.7.

Not applicable

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

#### **SECTION 16: Other information**

Issue date : 28/08/2020 Revision date : 29/08/2022

Full text of H-statements:

H220	Extremely flammable gas.

28/08/2020 EN (English) 7/8

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### SDS South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

28/08/2020 EN (English) 8/8