

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 11/16/2021 Revision date: 11/16/2023 Version: 1.0

## **SECTION 1: Identification**

### **1.1. Product identifier**

Product form Trade name Type of product Product code Product group : Mixture

- : Fozzi's foam for fun Groovy Green L
- : Kids bath product
- : 208014002, 214987001, 222885001, SH828, SH988, SH1258
- : Trade product

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

:

#### Use of the substance/mixture

1.3. Supplier's details

#### Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni – Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark

### **1.4. Emergency telephone number**

Emergency number

: (011) 421 7111

SECTION 2: Hazards identification	۱
2.1. Classification of the substance or	r mixture
Classification according to the United Nation Aerosol, Category 3 Skin corrosion/irritation, Category 3 Serious eye damage/eye irritation, Category 2 Hazardous to the aquatic environment — Acu Full text of H-statements: see section 16	H229 H316 A H319
2.2. Label elements	
Labelling according to the United Nations ( Hazard pictograms (GHS ZA) Signal word (GHS-ZA)	: Varning
Hazardous ingredients Hazard statements (GHS ZA)	<ul> <li>Alcohols, C10-16 ethoxylated, sulfates, sodium salts, propane, butane, liquefied, under pressure</li> <li>H229 - Pressurised container: May burst if heated.</li> <li>H316 - Causes mild skin irritation</li> <li>H319 - Causes serious eye irritation.</li> <li>H402 - Harmful to aquatic life</li> </ul>
Precautionary statements (GHS ZA)	<ul> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P251 - Do not pierce or burn, even after use.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P273 - Avoid release to the environment.</li> <li>P280 - Wear eye protection, protective clothing, protective gloves.</li> </ul>

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

	<ul> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P332+P313 - If skin irritation occurs: Get medical advice.</li> <li>P337+P313 - If eye irritation persists: Get medical advice.</li> <li>P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.</li> <li>P501 - Dispose of contents and container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.</li> </ul>
2.3. Other hazards	
Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated, Causes mild skin irritation, Causes serious eye irritation, Harmful to aquatic life

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

### Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	CAS-No.: 106-97-8	5.0 - 10.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401
propane	CAS-No.: 74-98-6	1.0 - 5.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
Alcohols, C10-16 ethoxylated, sulfates, sodium salts	-	1.0 - 5.0	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412

## SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effe	ects, both acute and delayed
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

5.2. Special hazards arising from the subst	ance or mixture
Explosion hazard Hazardous decomposition products in case of fire	<ul><li>Pressurised container: May burst if heated.</li><li>Toxic fumes may be released.</li></ul>
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release m	easures
6.1. Personal precautions, protective	equipment and emergency procedures
No additional information available	
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for contain	ment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and stora	age
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, in	cluding any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

propane (74-98-6)	
South Africa - Occupational Exposure Limits (Airl	oorne Pollutants)
Local name	Propane
OEL TWA	1800 mg/m <sup>3</sup>
OEL TWA [ppm]	1000 ppm
Regulatory reference	Government Notice No. R 904

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressu	:e (106-97-8)
South Africa - Occupational Expos	re Limits (Recommended Limits)
Local name	Butane
OEL TWA	1430 mg/m <sup>3</sup>
OEL TWA [ppm]	600 ppm
OEL STEL	1780 mg/m <sup>3</sup>
OEL STEL [ppm]	750 ppm
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Expos	re Limits (Airborne Pollutants)
Local name	n-Butane
OEL TWA	1430 mg/m <sup>3</sup>
OEL TWA [ppm]	600 ppm
OEL STEL	1780 mg/m <sup>3</sup>
OEL STEL [ppm]	750 ppm
Regulatory reference	Government Notice No. R 904

### 8.2. Appropriate engineering controls

## Appropriate engineering controls

Environmental exposure controls

: Ensure good ventilation of the work station.

- : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

## Hand protection Eye protection Skin and body protection Respiratory protection

: Protective gloves : Safety glasses : Wear suitable protective clothing : In case of insufficient ventilation, wear suitable respiratory equipment

# Personal protective equipment symbol(s):



#### 8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemic	al properties
9.1. Information on basic physical ar	d chemical properties
Physical state	: Liquid
Appearance	: Liquid.
Colour	: Green.
Odour	: Apple.
Odour threshold	: No data available
рН	: 5 – 7
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Auto-ignition temperature Decomposition temperature Flammability (solid, gas)	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> </ul>
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available

#### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Pressurised container: May burst if heated.

**10.2. Chemical stability** 

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

**10.4. Conditions to avoid** 

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

**10.5. Incompatible materials** 

No additional information available

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (oral) :	Not classified	
Acute toxicity (dermal) :	Not classified	
Acute toxicity (inhalation) :	Not classified	
propane (74-98-6)		
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))	
butane, liquefied, under pressure (106-97-8)		
LC50 Inhalation - Rat	1442.738 – 1443 mg/l 15 MIN	

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

butane, liquefied, under pressure (106-97-8)	
LC50 Inhalation - Rat [ppm]	800000 ppm 15 MIN
Skin corrosion/irritation	: Causes mild skin irritation. pH: 5 – 7
Serious eye damage/irritation	: Causes serious eye irritation. pH: 5 – 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Fozzi's foam for fun - Groovy Gree	L
Vaporizer	aerosol

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Hazardous to the aquatic environment, short-term : Ha (acute)	armful to aquatic life. armful to aquatic life.	
(chronic)	ot classified	
propane (74-98-6)		
LC50 - Fish [1] 24	24 mg/l (96 h, Pisces, Literature study)	
LC50 - Fish [2] 45	I9.9 mg/l (96 h, Pisces, Fresh water, QSAR)	
EC50 - Crustacea [1] 7	′ mg/l (48 h, Daphnia magna, Literature study)	
BCF - Fish [1] 9	9 – 25 (Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow) 1.	.09 – 2.8 (Experimental value, 20 °C)	
butane, liquefied, under pressure (106-97-8)		
LC50 - Fish [1] >	> 1000 mg/l (96 h, Pimephales promelas, QSAR)	
EC50 72h - Algae [1] 5.	5.3 – 5.5 mg/l (Algae, QSAR)	
Partition coefficient n-octanol/water (Log Pow) 2.	2.89 (Experimental value)	
12.2. Persistence and degradability		
Fozzi's foam for fun - Groovy Green L		
Persistence and degradability N	No additional information available	
propane (74-98-6)		
Persistence and degradability R	Readily biodegradable in water.	
butane, liquefied, under pressure (106-97-8)		
Persistence and degradability R	Readily biodegradable in water.	
12.3. Bioaccumulative potential		
Fozzi's foam for fun - Groovy Green L		
Bioaccumulative potential	No additional information available	

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

propane (74-98-6)		
BCF - Fish [1]	9 – 25 (Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
butane, liquefied, under pressure (106-97-8)		
Partition coefficient n-octanol/water (Log Pow)     2.89 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

# 12.4. Mobility in soil

Fozzi's foam for fun - Groovy Green L		
Mobility in soil	No additional information available	
propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Ecology - soil	Not applicable (gas).	
butane, liquefied, under pressure (106-97-8)		
Surface tension	< 0.1 N/m (0 °C)	
Partition coefficient n-octanol/water (Log Pow)	2.89 (Experimental value)	
Ecology - soil	Not applicable (gas).	
12.5. Other adverse effects		
Ozone	Not classified	

Other adverse effects

Not classifiedNo additional information available

# SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

# **SECTION 14: Transport information**

n accordance with SANS / IMDG / IATA		
SANS	IMDG	ΙΑΤΑ
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, non-flammable
14.3. Transport hazard class(es)		
2.2	2.2	2.2

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	ΙΑΤΑ
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		
14.6. Special precautions for user		
SANS Special provisions (SANS) Limited quantities (SANS) Limited quantities (SANS) Packagings, large packagings and IBCs Packing instructions (SANS) Packagings, large packagings and IBCs Special packing instructions (SANS)	<ul> <li>63, 190</li> <li>See SP277</li> <li>See SP277</li> <li>P003</li> <li>PP17, PP87</li> </ul>	
IMDG Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG)	<ul> <li>63, 190, 277, 327, 344, 381, 959</li> <li>P207, LP200</li> <li>PP87, L2</li> <li>F-D - FIRE SCHEDULE Delta - FLAMMABI</li> <li>S-U - SPILLAGE SCHEDULE Uniform - GA</li> <li>None</li> </ul>	LE GASES ISES (FLAMMABLE, TOXIC OR CORROSIVE)
IATA PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) CAO max net quantity (IATA) Special provisions (IATA) ERG code (IATA)	: E0 : Y203 : 30kgG : 203 : 75kg : 203 : 150kg : A98, A145, A167, A802 : 2L	

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

<b>SECTION 16: Other inform</b>	ation	
Issue date	: 16/11/2021	
Revision date	: 16/11/2023	

Full text of H-statements	
H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H227	Combustible liquid

# Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Full text of	H-statements
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H311	Toxic in contact with skin.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H316	Causes mild skin irritation
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.