



Specification:

1. Nominal pressure: 1.6MPa;
2. Working medium: Water, Gas, Oil (Non-corrosive);
3. Working temperature: -10°C to 120 °C;
4. Thread standard: according to ISO228-1;

NO.	PARTS	MATERIAL
4	BONNET	BRASS
3	O-RING	NBR
2	INSERT	BRASS
1	BODY	BRASS

CODE NO.	E	A	L	DN	SW	WEIGHT/G
330K025	1	75	13	24.5	37	240
330K032	1-1/4	81.5	12.5	27.5	47	340
330K040	1-1/2	86.5	16	33.5	53	450
330K050	2	98.5	18	38.5	65	640
330K065	2-1/2	129.5	22	48.5	82.5	1180
330K080	3	145	25	56.5	95	1870
330K100	4	166.5	28	72.5	125	3300

TOLERANCES	LIMIT DIMENSION					REMARK: 1.THE UNIT WEIGHT CAN BE ACCEPTED WITH IN ±2%. 2.THE TOLERANCE CAN BE ACCEPTED AS THE SHEET.	BRASS FOOT VALVE 25MM-100MM DATED: MAY 24, 2016
	>0-50	>50-60	>60-120	>120-200	>200-500		
ALL DIMENSIONS IN	±0.2	±0.3	±0.7	±1	±3		