



Specification:

1. Nominal pressure: 1.6MPa;
2. Working medium: Water, Gas, Oil (Non-corrosive);
3. Working temperature: -10°C to 120 °C;
4. Thread standard: according to ISO228-1;

| | | |
|----|------------|----------|
| 8 | handle | BRASS |
| 7 | press nuts | BRASS |
| 6 | gasket | PTFE |
| 5 | stem | BRASS |
| 4 | gasket | BRASS |
| 3 | seat | NBR |
| 2 | bonnet | BRASS |
| 1 | body | BRASS |
| NO | name | material |

| CODE NO. | E | DN | ØA | B | H | L | L1 | L2 | L3 | SW | SW1 | weight |
|------------|-----|----|------|------|----|----|------|----|----|------|------|--------|
| 333221-015 | 1/2 | 10 | 27 | 17.5 | 73 | 56 | 12.5 | 11 | 53 | 25.5 | 16.5 | 272 |
| 333221-020 | 3/4 | 13 | 30.5 | 17.5 | 86 | 63 | 15 | 12 | 53 | 33 | 19.5 | 407 |

| TOLERANCES | LINEAR-DIMENSION | | | | | REMARK: 1.THE UNIT WEIGHT CAN BE ACCEPTED WITH IN ±3%. 2.THE TOLERANCE CAN BE ACCETED AS THE SHEET. | BRASS STOP VALVE 15MM-20MM DATED:MAY 24, 2016 |
|-------------------|------------------|--------|---------|----------|----------|---|---|
| | >6-30 | >30-60 | >60-120 | >120-200 | >200-300 | | |
| ALL MACHININGS mm | ±0.2 | ±0.3 | ±0.7 | ±1 | ±3 | | |