



- Specification:**
1. Nominal pressure: 1.6MPa;
 2. Working medium: Water, Gas, Oil (Non-corrosive);
 3. Working temperature: -10°C to 120 °C;
 4. Thread standard: according to ISO228-1;

3	BONNET	BRASS
2	WEDGE	BRASS
1	BODY	BRASS
NO.	PARTS	MATERIAL

CODE NO.	E	A	H	D	L	SW	DN	WEIGHT/G
425K015	1/2"	47	30.5	27	12.5	24.5	12.5	115
425K020	3/4"	56	36	31	14	31	17.5	180
425K025	1"	63	45	39.5	14	38	22	290
425K032	1-1/4"	72.5	49	47	15.5	47.5	27	490
425K040	1-1/2"	80	52	51.5	15	53.5	31	620
425K050	2"	94	60.5	63.5	16	66	43.5	920
425K065	2-1/2"	102.5	70.5	74	16.5	83.5	53.5	1600
425K080	3"	124	80	89	20	97	62	2400
425K100	4"	160	103	118	26	124	89	4950

TOLERANCES	LIMIT DIMENSION				
	>6-30	>30-50	>50-120	>120-200	>200-500
ALL DIMENSIONS MM	±0.2	±0.3	±0.7	±1	±3

REMARK:
 1. THE UNIT WEIGHT CAN BE ACCEPTED WITH IN 3%
 2. THE TOLERANCE CAN BE ACCEPTED AS THE SHEET.

BRASS SWING CHECK VALVE
25MM-100MM
 DATED: MAY 24, 2016