## **Woodoc 10 Specification Sheet**



## **Typical Application:**

Suitable for general indoor applications. Woodoc 10 gives a fine finish that is heat-, stain-, alcohol- and water-resistant. Only for interior use. **Not suitable for use on floors.** 

## **Product Features:**

Woodoc 10 creates a clear, velvet finish and is the most popular sealer in the interior range. This sealer applies easily, and the gloss of the sealer may be infinitely varied, using different application techniques, from high gloss through "velvet" or semi-gloss, to absolute matt.

- Easy to apply.
- Penetrates wood, binds with it and lends a flexible yet strong and resistant surface finish.
- Suitable for all types of wood.
- Non-toxic once dry.
- Does not affect glue.
- Complete how-to-use instructions on label.

No: WD10/005 Dated: 14/08/12 Name: Woodoc 10 - Indoor Velvet Polywax Sealer **Description:** Smooth natural finish **Coverage:** First coat 10-12 m<sup>2</sup>/litre. Subsequent coats 12-14 m<sup>2</sup>/litre. 3 coats (average) 3,3 m<sup>2</sup>/litre. **Application:** Preferably by brush. Clean brush with mineral turpentine. **Dilution:** Not recommended. **Drving Time:** Drying will vary, depending on moisture and atmospheric conditions. **Product Properties:** Clear, lead-free, indoor wood sealer. Formaldehyde-Free. **Wax Content:** I ow. **Compatibility:** Mineral Turpentine. Non Compatibility: Acetone, Lacquer Thinners, Benzene and other solvents. **Packaging:** 500 ml, 1 litre, 2,5 litres and 5 litres. (20 or 200 litres available on request from dealer) ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE

## ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis. IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by: Rekara Mills (Pty) Ltd PO Box 16, Fort Beaufort 5720, South Africa Tel +2746 645 1109 Fax +2746 645 1538

Customer Service: Toll-Free during office hours 0800 411 200 (South Africa only) E-mail: information@woodoc.com or visit www.woodoc.com