Woodoc 20 Specification Sheet



Typical Application:

Apply Woodoc 20 to interior woodwork such as skirting boards, banisters, bar- and kitchen counters, doors and window frames where an extra hard, grain-filled surface with superior heat and stain resistance is required. Only for interior use.

Product Features:

Woodoc 20 is a clear, polyurethane sealer that gives a smooth, gloss finish that is heat-, stain-, water- and alcohol-resistant.

- Easy to apply.
- Penetrates wood, binds with it and lends a flexible yet strong and resistant surface finish
- Suitable for all types of wood.
- Non-toxic once dry.
- Does not affect glue.
- Complete how-to-use instructions on label.

No: WD20/004 **Dated:** 24/08/11

Name:

Woodoc 20 - Indoor Gloss Polyurethane Sealer

Description:

A glossy, "polished", grain filled finish.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

Preferably by brush. Clean brush mineral turpentine.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear, lead-free, indoor wood sealer.

Formaldehyde-Free

Wax Content:

None.

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

500 ml, 1 litre and 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis. IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by: Rekara Mills (Pty) Ltd PO Box 16, Fort Beaufort 5720, South Africa Tel +2746 645 1109 Fax +2746 645 1538