
PRODUCT INFORMATION AND SPECIFICATION SHEET

Product name : MEDIUM DUTY KELIFLEX SUCTION & DELIVERY HOSE

Description : Spirally reinforced PVC suction hose convoluted on the outside. Available in 30M lengths in opaque yellow.

Application : Suction and delivery of liquids and mixtures in sewage transfer, agriculture, mining, industrial, civils, fishing, dredging, etc.

Advantages : Super Flexible, UV stabilized smooth bore, full flow.
Abrasion, shock and crush resistant.
Temperature ranges 0 - 60 Celsius.
Non toxic PVC.
Can withstand vacuum.
PROUDLY MADE IN SOUTH AFRICA.

Specifications : MEDIUM DUTY KELIFLEX SUCTION & DELIVERY HOSE

ID (mm)	ID (inches)	Workir pressu (Kpa)	Bend rac (mm)	Weigh (Kg/M)	Weight Roll
25.4mm	1"	550	60	0.4	12
31.8mm	1.25"	550	70	0.5	15
38.1mm	1.5"	480	80	0.82	24.6
50.8mm	2"	480	90	1	30
63.5mm	2.5"	410	125	1.3	39
76.2mm	3"	380	215	1.7	51
101.6mm	4"	310	350	3	90



Disclaimer : The specifications listed are a guideline only, and the information provided may vary from time to time. All measurements indicated above are target spec, tolererance levels are within factory spec. We reserve the unconditional right to change the specifications, and will not be held liable for any loss, injury or damage whatsoever